

SPECIFICATIONS

GENERAL

Self-contained, electric refrigerated, floor model water cooler. Capacity of 50°F drinking water, based upon 80°F inlet water and 90°F ambient.

Non-pressurized tube-on-tube system is standard. Non-pressurized cooling coil is located after bubbler valve, so that cooling coil is subject to line pressure only when valve button is pressed.

NO LEAD DESIGN

THIS WATER COOLER COMPLIES WITH THE LEAD-FREE DEFINITION IN THE SAFE DRINKING WATER ACT OF 1986 AND LEAD CONTAMINATION CONTROL ACT OF 1988.

Elkay Water Coolers are manufactured with a waterway system utilizing copper components and completely lead-free materials. These waterways have no lead because all lead materials, such as leaded brass, have been removed. All joints are brazed using silver solder only. No lead solder is permitted. A strainer with an easily cleanable screen is provided to allow trapping and convenient removal of water born particulate of 140 microns and larger prior to their entry into the water cooler.



This water cooler is classified by Underwriters Laboratories Inc. in accordance with ANSI/NSF61, Section 9-1997b.

CAPACITIES CHART

Model	Base	*GPH of 5 °F Drinking Water Room Temperature °F			Rated	Full Load	Glass Filler	Ship. Wt.
Number	Rate	7 °F	8 °F	9 °F	Watts	Amps	Option	Lbs.
EFY8	8.0	10.2	9.6	8.0	400	5.0	NO	81

^{*}Based on 80°F inlet water temperature.

Rated watts shown are based on operational (run) time, in accordance with A.R.I. Standard 1010 conditions. Specific applications will determine the actual watts consumed per hour. Watts consumed will be based on number of people served per hour (usage), ambient temperatures, and inlet water temperature.

COOLING SYSTEM

Motor Compressor: Hermetically sealed, reciprocating type, 115V, 60 Hertz single phase. Sealed in lifetime oil supply.

Electrical: Requires 1/2" I.P.S. rigid conduit into junction box inside cabinet (hole provided).


Condenser: Water cooled.

Cooling Unit: Tube-on-tube type all copper counterflow design. Fully insulated with EPS foam which meets Underwriters Laboratories Inc. requirements for self extinguishing material.

Refrigerant Control: Refrigerant HFC-134a is controlled by accurately calibrated capillary tube for positively trouble free performance.

Temperature Control: Enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements.

UL Listed: Listed by Underwriters Laboratories Inc. under Water Coolers, for use in Hazardous Locations in following classes: Flammable Gases or Vapors, Class I, Groups C and D; Combustible Dust, Class II, Groups E, F and G; and Ignitable Fibers of Flyings, Class III, as described in articles 500-5, 500-6 and 500-7 of the National Electrical Code (includes Division 1 and 2 for each class). Class I Temperature T4A. All wiring, wiring devices, controls, etc., are in UL Listed enclosures and conduits.



CONSTRUCTION

Fountain Top: One piece stainless steel top.

Stream Projector: Separate push button control. Stream projector with protective hood meets all sanitary codes and has inline flow regulator from 20 to 105 psi.

Removable Panel: Removable front panel offers easy accessibility to interior.

Color Selection: Stainless steel furnished as standard.

Cabinet: Cabinet design allows for flush to wall mounting, or free standing.

5 YEAR LIMITED WARRANTY on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. Sample Certificate available on request.

Elkay Pressure-Type Water Coolers are designed to operate on 20 psi to 105 psi supply line pressure. If inlet pressure is above 105 psi, a pressure regulator must be installed in the supply line. Any damage caused by reason of connecting this product to supply line pressures lower than 20 psi or higher than 105 psi is not covered by the warranty.

Note: In keeping with our policy of continuing product improvement, Elkay reserves the right to change materials, design and specifications without notice.

Elkay Electric Water Cooled Water Coolers are listed by Underwriters Laboratories Inc., approved by C.S.A., rated in accordance with A.R.I. Standard 1010 and meet all known federal and state plumbing codes.







9-1E