



## Sports Bottle Filler

### M8SBF

#### Suggested Specification

Model M8SBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Basin shall be designed to eliminate splashing and standing water. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards. Shall comply with ANSI/NSF 61.

#### Models

**M8SBF** delivers 8.0 gallons of chilled drinking water per hour. These models satisfy CABO/ANSI A117.1. Models also meet guidelines for children's accessibility providing the floor to orifice height is 30 inches and proper clear floor space is provided for frontal approach.

#### Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are lead-free in materials & construction
- > Heavy Duty steel frame
- > High Efficiency cooling tank and coil
- > Refrigerant R-134a



Certified to  
NSF/ANSI 61/Section 9



#### Finishes

- > Standard cabinet finish: Brushed Stainless Steel
- > Optional cabinet finish: Regency Bronze

#### Options (at additional cost)

- > Ultra Violet filtration
- > Oasis Green Filtration system

#### Installation

- > Prior to roughing, consult with local, state and federal codes for proper mounting height
- > Shipped with complete instructions and wall mounting bracket
- > Removable front panels allow for easy access to filtration and refrigeration unit.



ADA Compliant when installed in an alcove, or with an accessory apron, or with a right wing wall for a right high unit or left wing wall for a left high unit.



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Models covered by this specification complies with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.

