



BARRIER-FREE VERSACOOLER® II
Energy and Water Conservation Technology

PG8AC, PGAC
Mechanical Activation

Suggested Specification

Model PG8AC shall be for Green Specified construction, deliver 8.0 gph of 50° F water at 90° F ambient and 80° F inlet water. Model PGAC is a non-refrigerated drinking fountain and delivers ambient water. Models PG8AC and PGAC shall include front and side push pads to shall be Mechanically Activated. Basin shall be designed to eliminate splashing and standing water. Water Saver Bubbler reduce waste water by 50% and shall have a flexible guard and operate between 20 and 120 psi. Cabinet finish shall be Sandstone powder coated paint on galvanized steel or brushed stainless steel. New High Efficient positive start compressor and cooling system shall use R-134a refrigerant, fully insulated and controlled by positive sensing thermostat. Shall comply with ANSI A117.1 and ADA. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards. Shall comply with ANSI/NSF 61.

Models

PG8AC delivers 8.0 gallons of chilled drinking water per hour. **PGAC** is a non-refrigerated fountain. These models satisfy CABO/ANSI A117.1. This cooler will comply with ADA guidelines when properly installed. Models also meet guidelines for children's accessibility providing the floor to orifice height is 30 inches and proper clear floor space is provided for frontal approach.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are lead-free in materials & construction
- > Stainless Steel top
- > Flexible, one-piece Water Saver Bubbler guard
- > Heavy Duty galvanized steel frame
- > New High Efficiency cooling system
- > Refrigerant R-134a
- > Product Certified to NSF/ANSI Standard 61, Annex G (AB1953)
- > Four push pad Mechanical activation electricity not required
- > External stream height adjustment

Finishes

- > Standard cabinet finish: Sandstone powder coated paint on steel
- > Optional finishes (at additional cost): Stainless Steel, Regency Bronze, and optional powder coated finishes

Options (at additional cost)

- > Glass Fillers (factory installed)
- > Push Handle (029603-004)
- > Push Back (029603-005)
- > Push Down (029603-006)
- > Filtration System 100% Biodegradable
- > Stainless Steel Bubbler

Installation

- > Prior to roughing, consult with local, state and federal codes for proper mounting height
- > Shipped with complete instructions and wall mounting bracket
- > Removable side and front panels provide easy access for installation



ADA Compliant for both adult or child when properly installed.



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on the sealed refrigeration system and most component parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of <=0.25%) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953).

Models covered by this specification complies with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.



Certified to NSF/ANSI 61-G

Model	50° F Drinking Water 90° F Ambient Air Temperature*			Hot 'N Cold™ Model	115 Volts, 60 Hz			Glass Filler Acces. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
PG8AC**	8.0	8.0	No	No	1/4	3.1	286	Yes	Yes	59 lbs.
PGAC								Yes	Yes	25 lbs.

* Industry Standard Rating Condition 80°F inlet water temperature

** Special export models available, operable on 220-240 volts, 50/60 Hz

OASIS™ BARRIER-FREE Versacooler® II MODELS PG8AC, PGAC, PG8ACEE, PGF8AC, PGFAC, PGF8ACEE, PGV8AC

